MIRANOL[®] ULTRA L-32

TECHNICAL DATA SHEET NA 90006150 - JUNE 2021

IDENTIFICATION

Chemical Name: SODIUM LAUROAMPHO ACETATE

CAS Number: 68608-66-2

SPECIFICATIONS	RESULTS	METHOD
Color Gardner	3 Max	RP-0138
Viscosity @ 25 C, CPS	5000 Max	RP-0596
Appearance	Clear, Clean Liquid	RP-0064
Solids (Moisture Balance), %	38.0 - 39.0	RP-0536
pH (20% Solution)	9.0 – 9.5	RP-0420
Active, %	30.0 – 32.0	Calc
Sodium Chloride, %	7.6 Max	RP-0097
Sodium Glycolate, %	1.8 Max	RP-0108
Amidoamine, %	1.0 Max	RP-1186

TYPICAL PROPERTIES

Stability Solubility Compatibility Specific gravity Stable in strong acid, neutral and strong alkaline solutions. Soluble in water and ethanol. Excellent compatibility with anionic, nonionic and cationic surfactants. 1.17

STANDARD APPLICATIONS

MIRANOL[®] ULTRA L-32 can be used in laundry, liquid dish detergent and hard surface cleaner formulations. It functions as a mild emulsifier, solubilizer and foaming agent. Its high foaming property and ability to reduce the irritation of other surfactants finds use in both liquid dish detergents and liquid hand soaps. Due to its wide pH stability it can be used in a variety of acidic or alkaline hard surface cleaners. It is also use in liquid prespotter and liquid laundry formulations.

STANDARD PACKAGING

MIRANOL[®] ULTRA L-32 is available in Bulk, 200 KG. Plastic Drums, 500 LB. / 227 KG. Closed Head Poly Drums, 2200 LB. Totes, and 1000 kg. Plastic IBCs. Alternative package sizes may be available upon request.

SHELF LIFE

MIRANOL® ULTRA L-32 has a shelf life of 365 days.

WARNING

The information contained in this document is given in good faith and based on our current knowledge. It is only an indication and is in no way binding, notably as regards infringement of or prejudice to third parties through the use of our products. SOLVAY GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS.

This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of the present document and SOLVAY is at their disposal to supply any additional information.



For orders or questions, call us at the following numbers or visit us at <u>www.solvay.com</u>

North America 1-888-776-7337 Europe – Middle East – Africa (33) 01 53 56 50 00 Asia - Pacific (65) 62 91 19 21 Latin America (55) 11 37 47 78 86